

CONSERVATION PRACTICE STANDARD

CHANNEL STABILIZATION

(Ft.)

CODE 584

DEFINITION

Measure(s) used to stabilize the bed or bottom of a channel

PURPOSE

This practice may be applied as part of a conservation management system to support one or more of the following:

- Maintain or alter channel bed elevation or gradient
- Modify sediment transport or deposition
- Manage surface water and ground water levels in floodplains, riparian areas, and wetlands.

CONDITIONS WHERE PRACTICE APPLIES

This practice applies to the beds of existing or newly constructed channels, alluvial or non-alluvial, undergoing damaging aggradation or degradation that cannot be feasibly controlled by clearing or snagging, by the establishment of vegetative protection, by the installation of bank protection, or by the installation of upstream water control measures.

CRITERIA

Measures shall be designed and installed according to a site-specific plan, and in accordance with all local, state, and federal laws and regulations.

Measures to be applied shall be compatible with improvements planned or being carried out by others.

Sufficient depth shall be maintained to provide adequate outlets for subsurface drains, tributary streams or ditches, or other channels.

Effect of channel work on existing structures such as culverts, bridges, buried cables, pipelines, and irrigation flumes shall be evaluated to determine impact on their intended functions.

An assessment of channel stabilization needs should be considered in sufficient detail to identify the causes contributing to the instability (e.g. watershed alterations resulting in significant modifications of discharge or sediment production). Due to the complexity of such an assessment, use of an interdisciplinary team should be considered.

The quantity and character of the sediments entering the reach of channel under consideration shall be analyzed on the basis of both present conditions and projected conditions caused by changes in land use or land treatment, and upstream improvements or structural measures.

Measures shall be designed to account for all load conditions, including, but not limited to: flow duration, depth of inundation, buoyancy, uplift, scour, angle of attack, stream velocity anticipated ice action, debris impact and fluctuating water levels.

Measures shall be compatible with the bank materials, water chemistry, channel hydraulics, and slope characteristics, both above and below the water line.

Spoil material from clearing, grubbing, and channel excavation shall be disposed of in a manner that will not interfere with the function of the channel.

All disturbed areas around measures shall be protected from erosion. Vegetation shall be selected that is best suited for the anticipated site conditions.

Measures applied shall avoid adverse effects to endangered, threatened, and candidate species and their habitats, whenever possible.

Measures applied shall avoid adverse effects to archaeological, historic, structural, and traditional cultural properties, whenever possible.

Channel clearing to remove stumps, fallen trees, debris, and bars shall only be done when they are causing or could cause detrimental bank erosion or structural failure. Habitat forming elements that provide cover, food, pools, and water turbulence shall be retained or replaced to the extent possible.

Measures shall be functional for the design flow and sustainable for higher flow conditions based on acceptable risk.

Measures shall be designed to maintain the appropriate sediment transport regime in order to avoid detrimental erosion or sedimentation upstream and downstream.

Measures shall not result in adverse affects on the function of the stream or the stream corridor.

When flood hazards are a concern, the effects of protective measures shall not cause detrimental changes in water surface elevations.

CONSIDERATIONS

Consider area- and watershed-wide planning for proper design, function and management of protective measures where the design reach involves multiple stakeholders.

When designing protective measures, consider the changes that may occur in the watershed hydrology and sedimentation over the design life of the measure. Where feasible, utilize natural channel design methods that are compatible with fluvial geomorphology.

Consider utilizing woody debris removed during construction in the overall practice design.

Measures should consider habitat and migration needs of aquatic species.

Consider maintaining or improving the habitat value for fish and wildlife, which includes lowering or moderating water temperature, and improving water quality.

Consider opportunities to improve habitat for threatened, endangered, and other species of concern, where applicable.

Consider maximizing adjacent wetland functions and values with the project design and minimizing adverse effects to existing wetland functions and values.

Consider protecting side channel inlets and outlets from erosion or sedimentation.

Consider the type of human use and safety aspects when designing the protective measures. Specifically, measures should be designed to minimize safety hazards to boaters, swimmers, or people using the channel.

Use construction materials, grading practices, vegetation, and other site development elements that enhance aesthetics, recreational use, and maintain or complement existing landscape uses such as pedestrian paths, climate controls, and buffers. Avoid excessive disturbance and compaction of the site during installation.

PLANS AND SPECIFICATIONS

Plans and specifications for this practice shall be prepared for specific channel reaches and field sites and shall describe the requirements for applying the practice to achieve its intended purpose(s).

OPERATION AND MAINTENANCE

The owner or others responsible for operating and maintaining the system shall prepare an operation and maintenance plan. The plan shall provide specific instructions for operating and maintaining the system to insure that it functions properly. It shall also provide for periodic inspections and prompt repair or replacement of damaged components.